

AMS 111 Compact

IoT Logger

AMS 111 Compact is optimized for applications with a reduced set of sensors and applications where portability is important. It runs on a globally trusted multitasking operating system and provides a rich set of features. Despite its small size, it provides flexibility and performance comparable to the AMS 111 loggers. The most compact variant fits into a box with dimensions of 15 x 10 x 7 cm.



Interchangeable
communication module
[LoRA, 3G GSM, 4G GSM,
LTE NB1/M1]



4 universal I/O ports,
USB port
SDI-12
RS-485



Optional integrated
battery with charger



SD memory card data
logging

AMS 111 Compact provides a large set of functions in the basic configuration and can be further expanded with optional modules. The basic configuration contains three serial ports (RS-232, RS-485, and SDI-12), a USB port, built-in internal non-volatile memory, micro SD memory card, 4G GSM modem,

4 universal inputs/outputs ports, and 4 switchable power outputs. AMS 111 Compact has a built-in solar charger with the MTTP algorithm. The logger can be customized and programmed using a user-friendly graphical interface or directly with JSON-based scripts.

Interfaces and storage

Serial port	RS-232 (with HW flow control), RS-485 (optionally isolated), SDI 12 (v1.3)
USB	virtual serial port, mass storage
Bluetooth (optional)	version 5.2
Modem	built-in 4G module
Storage	micro SD card, internal non-volatile memory

4G modem**Data rates**

- LTE-FDD Max 100 Mbps (DL) Max 50 Mbps (UL)
- LTE-TDD Max 61 Mbps (DL) Max 18 Mbps (UL)
- DC-HSPA+ Max 42 Mbps (DL) Max 5.76 Mbps (UL)
- UMTS Max 384 Kbps (DL) Max 384 Kbps (UL)
- TD-SCDMA Max 4.2 Mbps (DL) Max 2.2 Mbps (UL)
- CDMA Max 5.4 Mbps (DL) Max 14.7 Mbps (UL)
- EDGE Max 236.8 Kbps (DL) Max 236.8 Kbps (UL)
- GPRS Max 85.6 Kbps (DL) Max 85.6 Kbps (UL)

Operating temperature range

–40 °C to +85 °C

Environmental conditions

Operating temperature range: –40 °C to +70 °C

Operating humidity range: 0 to 100 %

Universal configurable IO ports**Quantity**

4

Functionalities

digital input, digital output, analog input (16-bit), Low power impulse counter (1 port), measuring 4 - 20 mA loop (1 port)

Power outputs**Quantity**

4

Parameters

configurable, maximal current 200 mA for each output and in Li-ion version the total output sourcing is up to 500 mA at 12 V

User interface**Status LEDs****USB virtual serial port with command set****Optional Bluetooth serial interface with command set****Optionally built-in OLED with keypad****Power options****Built-in charger with MTTP algorithm****Battery**

Li-ion accumulator with monitoring and USB charging or 12/24 V lead-acid accumulator with monitoring

Backup battery for low drift RTC**Optional features****Built-in GNSS module****Safety door switch sensor****Door padlock****Display****Optional extension modules****Serial module (2x RS-232 / 2x RS-485)****Ethernet module****Precise AD module****Communication modules (4G, Lora)**

Electrical parameters

External power in Li-ion power version	5 V to 30 V (AC/DC, PV panel)
External power in 12 V Pb accumulator power version	15 V to 30 V (AC/DC, PV panel)
Consumption in sleep mode	0.37 mW
Consumption in active mode	depending on the configuration

Environmental parameters

Temperature	-40 – 70 °C
Humidity	0 – 100 % non-condensing
Protection	IP 67



ISO Quality Certified Company

All specifications are subject to change without prior notice.
© MicroStep-MIS. All rights reserved.
www.microstep-mis.com