

TRwS214/514/215/415

Total Rain Weighing Sensor

Total Rain weighing Sensor TRwS with its original mechanical and electronic design is excellent tool to measure all types of precipitation within wide temperature range, harsh wind and snow conditions. TRwS is most sensitive and very accurate rain gauge. Simple mechanical construction together with very sophisticated firmware can guarantee perfect performance. TRwS is available with apertures of 200 cm², 400 cm² and 500 cm².




Weighing sensor



Rain and snow precipitation gauge



High precision



Reliable

Rain and snow precipitation gauge

Measurement

- Solid and liquid precipitation
- One-minute intensity
- Total sum of precipitation
- Rain duration

Elimination of

- Wind vibration
- Particles
- Unreal step change of weight
- Evaporation
- Temperature fluctuation

Output signals

- Contact
- Serial RS-485 / SDI-12

Options

- Air temperature measurement
- Rain detector
- Wind speed assessment
- Corrected data eliminating wind influence

Features

- Extra low consumption < 45 mW
- Easy maintenance
- Evaluation and control of accuracy "in situation"
- Auto diagnostic and self-check
- Orifice heating included
- Direct replacement of tipping bucket rain gauge
- Heating for icing elimination included
- Fulfills all WMO recommendations

General specifications

	TRwS214	TRwS514	TRwS215	TRwS415
Orifice area	200 cm ²	500 cm ²	200 cm ²	400 cm ²
Range of precipitation	750 mm	250 mm	1500 mm	750 mm
Accuracy	0.1 %			
Maximum rain intensity	120 mm / min			
Resolution	0.001 mm			
Measuring element	strain-gauge bridge			

Mechanical specifications

Dimensions	360 mm x 540 mm	360 x 380 mm	385 x 650 mm	385 x 610 mm
Weight	8 kg		9.5 kg	
Materials (3 different)	top part: UV stabilized fiberglass	bottom part: stainless steel	base: aluminum alloy	

Electrical and interface specifications

Power supply	8 to 24 V DC / max 15 mA
Heating supply	12 V / 1 A (option 24 V / 1A)
Output contact (1 / 0.1 / 0.01 mm)	$U_{\max} = 30 \text{ V}, I_{\max} = 300 \text{ mA}$
Serial output	RS-485 / SDI-12

Environmental specifications

Operating temperature range	-40 °C to +70 °C
Operating humidity range	0 to 100 %
Degree of protection	IP 65

Options

Air temperature measurement	-40 °C to +70 °C
Wind speed estimation	extra value
Wind correction	yes
Wind shield	yes